



## C66

### Mobile Computer



Android



4G



WiFi



Bluetooth



1D Barcode



2D Barcode



NFC



UHF



Camera



GPS

Chainway C66 is a newly-developed rugged handheld computer with large screen and strong extensibility. Based on Android 7.1 OS, it is equipped with Qualcomm octa-core processor for high-speed processing. With 5.45-inch high-definition display, it is integrated with barcode scanning, NFC and other functions. The data collection device supports quick charge and UHF sled for good extensibility that can meet the needs in logistics, warehouse, manufacturing, retail, asset tracking, power patrol inspection, etc.



UHF



UHF Sled Reader



Pistol Grip

# Specification

## Physical Characteristics

<b>Dimensions</b>	160x76x15.5mm / 6.3*2.99*0.61in
<b>Weight</b>	287g/ 10.12oz( Host with battery)
<b>Keypad</b>	1 power key ,2 scan keys ,2 volume keys ,1 PTT key
<b>Battery</b>	4300mAh removable main battery, 5200mAh removable pistol battery, support QC3.0 Standby: over 300 hours (only main battery) Continuous use: over 12 hours (depending on user environment) Charging time: 2.5hours (charge device by standard adaptor and USB cable)
<b>Speaker</b>	Support
<b>Vibrator</b>	Support
<b>Microphone</b>	2 Microphones, 1 for noise reduction
<b>Display</b>	5.45-inch display, IPS LTPS 1440*720
<b>Touch Panel</b>	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
<b>Sensor</b>	Distance sensor, light sensor, gravity sensor
<b>Indicator LED</b>	Power, charging, status indicator
<b>Card slot</b>	2 slot for SIM card, 1 slot for TF card
<b>Interfaces</b>	USB3.0, Type-C, OTG, extended thimble

## Performance

<b>CPU</b>	Qualcomm 2.0GHz Octa-core
<b>RAM+ROM</b>	2GB+16GB / 3GB+32GB
<b>Expansion</b>	Supports up to 128 GB Micro SD card

## Developing Environment

<b>Operating System</b>	Android 7.1
<b>SDK</b>	Chainway Software Development Kit
<b>Language</b>	Java
<b>Tool</b>	Eclipse / Android Studio

## User Environment

<b>Operating Temp.</b>	-20°C~+50°C
<b>Storage Temp.</b>	-40°C~+70°C
<b>Humidity</b>	5%RH - 95%RH non condensing
<b>Drop Specification</b>	Multiple 1.5m/4.9ft drops (at least 20 times) to the concrete across the operating temperature range Multiple 2.4m/7.87ft drops (at least 20 times) to the concrete after installed rubber bumper
<b>Tumble Specification</b>	1000 x 0.5m/1.6ft falls at room temperature
<b>Sealing</b>	IP65 per IEC sealing specifications
<b>ESD</b>	±15KV air discharge, ±8KV conductive discharge

## Communication

<b>WLAN</b>	Support 802.11 a/b/g/n/ac
<b>WWAN (Europe, Asia)</b>	2G: 850/900/1800/1900MHz 3G: CDMA EVDO: BC0 WCDMA: 850/900/1900/2100MHz TD-SCDMA: A/F(B34/B39) 4G: B1, B3, B5, B7, B8, B20, B38, B39, B40, B41

<b>WWAN(America)</b>	2G: 850/900/1800/1900MHz 3G: 850/900/1900/2100MHz 4G: B2, B4, B5, B7, B12, B17, B38
<b>Bluetooth</b>	Bluetooth 4.2/4.1+HS/4.0/3.0+HS/2.1+EDR
<b>GNSS</b>	GPS/AGPS, GLONASS, BeiDou, internal antenna

## Data Collection

### Camera

<b>Rear Camera</b>	Rear 13MP Autofocus with flash
--------------------	--------------------------------

### NFC

<b>Frequency</b>	13.56MHz
<b>Protocol</b>	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
<b>Chips</b>	M1 card (S50, S70), CPU card, NFC tags, etc.
<b>Range</b>	2-4cm

### UHF1 (Optional)

<b>Engine</b>	CM2000-1 module based on Impinj Indy R2000
<b>Frequency</b>	865MHz-868MHz / 920-925MHz / 902-928MHz
<b>Protocol</b>	EPC C1 GEN2 / ISO18000-6C
<b>Antenna</b>	Circular Polarized Antenna (4dBi)
<b>Power</b>	1W (30dBm, +5dBm to +30dBm adjustable) 2W Optional (33dBm, for Lati America, etc.)
<b>R/W range</b>	>25m (indoors); >10m (open outdoors)
<b>Reading rate</b>	>200 tags/s
<b>R/W range</b>	>25m (indoors); >10m (open outdoors)
<b>Communication Mode</b>	Pin Connector

### UHF2 (Optional, UHF Sled)

<b>Engine</b>	CM2000-1 module based on Impinj Indy R2000
<b>Frequency</b>	865MHz-868MHz / 920-925MHz / 902-928MHz
<b>Protocol</b>	EPC C1 GEN2 / ISO18000-6C
<b>Antenna</b>	Circular Polarized Antenna (3dBi)
<b>Power</b>	1W (30dBm, support +5~+30dBm adjustable) 2W Optional (33dBm, for Lati America, etc.)
<b>R/W range</b>	>22m(indoors);>8m(open outdoors)
<b>Communication Mode</b>	Pin Connector / Bluetooth

\*Ranges and rates depend on tags and environment

### Barcode Scanning (optional)

<b>2D Scanner</b>	Zebra: SE4710/SE2100; Honeywell: N6603
<b>1D Symbolologies</b>	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
<b>2D Symbolologies</b>	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX),etc.

### Optional accessories(See details in Accessory Guide)

Separate handle with one button;
Handle + battery (handle battery 5200mAh, one button) ;
UHF back clip + handle (5200mAh, one button) ;
Wrist Strap; Rubber Bumper; Charging Cradle

Notice: Product specifications are subject to change without prior notice. / Model: C66 / Update Date: 2019-05-27

**CHAINWAY®**

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net