



F110 FULLY RUGGED TABLET

- Enhanced Enterprise Security with Optional Intel vPro, Windows Hello Face-authentication Camera, TPM 2.0 and Many More Multi-Factor Authentication Options
- 8th Generation Intel[®] Core[™] i7/i5 Processor
- 11.6" LumiBond[®] 2.0 Display with Getac Sunlight Readable Technology and Capacitive Touchscreen
- 6 Configurable Options to Fit Diverse Data Collection Needs: Optional 1D/2D Imager Barcode Reader/Serial Port/Ethernet/ 2nd USB (USB 2.0) Port/Serial Port+Ethernet
- LifeSupport[™] Battery Swappable Technology



Rugged Mobile Computing Solutions

Specifications

Operating System Windows 10 Pro

Mobile Computing Platform Intel® Core[™] i5-8265U Processor 1.6GHz Max. 3.9GHz with Intel® Turbo Boost Technology - 6MB Intel[®] Smart Cache

Platform Options: Intel® Core™ i5-8365U vPro™ Processor 1.6GHz Max. 4.1GHz with Intel® Turbo Boost Technology 6MB Intel[®] Smart Cache

Intel® Core[™] i7-8565U Processor 1.8GHz Max. 4.6GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache

Intel[®] Core[™] i7-8665U vPro[™] Processor 1.8GHz Max. 4.8GHz with Intel[®] Turbo Boost Technology - 8MB Intel[®] Smart Cache

VGA Controller

Intel[®] UHD Graphics Display 11.6" IPS TFT LCD FHD (1920 x 1080) Protection film 800 nits LumiBond[®] display with Getac sunlight readable technology Capacitive multi-touch screen

Storage & Memory

8GB DDR4 Optional: 16GB / 32GB DDR4 256GB SATA SSD Optional: 512GB / 1TB SATA SSD Optional: 256GB / 512GB / 1TB PCIe NVMe SSD

Kevboard

Power button 5 tablet programmable buttons

Pointing Device

Touchscreen

- Capacitive multi-touch screen - Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional: 1D/2D Imager Barcode Reader, or serial port, or LAN (RJ45), or USB 2.0 port, or serial port + LAN (RJ45)

I/O Interface

FHD webcam x 1 × 8M pixels auto focus rear camera x 1 Headphone out/Mic-in Combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 HDMI x 1 Docking Connector x 1 Optional: Windows Hello face-authentication camera (front-facing) x 1 Optional: RF antenna pass-through for GPS, WLAN and WWAN

Communication Interface

Intel® Dual Band Wireless-AC 9260, 802.11ac Bluetooth (v5.1) $^{\rm ii}$ Optional: Dedicated GPS Optional: 4G LTE mobile broadband Optional: 10/100/1000 base-T Ethernet ⁱ (occupies expansion slot)

Security Feature

TPM 2.0 Kensington Lock Optional: Intel® vPro[™] Technology Optional: LF/HF RFID reader [™], v, or HF RFID reader [™], or Smart Card Reader, or Fingerprint scanner

Power

AC Adapter (65W, 100-240VAC, 50/60Hz) Li-Ion smart battery (11.4V, typical 2160mAh; min. 2100mAh) x 2 LifeSupport[™] battery swappable technology

Dimension (W x D x H) & Weight

314 x 207 x 24.5mm (12.4" x 8.15" x 0.96") 1.39kg (3.08lbs) ^{vii}

Rugged Feature MIL-STD-810H certified

IP65 certified MIL-STD-461G certified viii Vibration & 4 feet (1.2m) drop resistant ^{xiii}

e-Mark certified for vehicle usage Optional: ANSI / UL 121201, CSA C22.2 NO. 213 ^{xii} **Environmental Specification**

Temperature ⁱ

- Operating: -29°C to 63°C / -20°F to 145°F Storage: -51°C to 71°C / -60°F to 160°F Humidity
- 95% RH, non-condensing

Pre-installed Software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager ^{xi} Optional: Absolute Persistence® Accessorie Battery (11.4V, typcial 2160mAh; min. 2100mAh) AC Adapter (65W, 100-240VAC) Capacitive Stylus

Optional:

Carry Bag Tablet Folio Case Battery (11.4V, typcial 2160mAh; min. 2100mAh) Multi-Bay Charger (Dual Bay) Multi-Bay Charger (Eight-Bay) Detachable Folding Keyboard AC Adapter (65W, 100-240VAC) Office Dock AC Adapter (90W, 100-240VAC) MIL-STD-461 Certified AC Adapter (90W, 115-230VAC) Vehicle Adapter (120W, 11-32VDC) Digitizer Pen Capacitive Stylus Protection Film Hand Strap Shoulder Strap (2-point) Shoulder Harness (4-point; handsfree) Vehicle Cradle Vehicle Dock Office Dock

Office Dock with Twin Battery Charger

Bumper-to-Bumper Warranty Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. Standard

3 years Bumper-to-Bumper

- Barcode reader, serial port, Ethernet, 2nd USB (USB 2.0) port, or serial port+Ethernet are
- mutually exclusive options. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is
- operating in the area. iii LF/HF RFID reader, HF RFID reader, smart card reader and fingerprint scanner are mutually
- exclusive options.
 iv LF(125kHz) / HF(13.56MHz) Combo RFID / NFC reader(iClass, HID Prox, ISO 15693, 14443 A/B, Mifare and FeliCa[™] compliant).
 V LF(HF RFID reader option is not Energy Star 8.0 compliant)
- compliant.
- 13.56MHz Contactless HF RFID reader (ISO 15693, vi

- vi 13.56MHz Contactless HF RFID reader (ISO 15693 14443 AVB, Mifare and FeliCa[™] compliant).
 vii Weight and dimensions vary from configurations and optional accessories.
 viii MIL-STD-461 90W AC adapter sold separately.
 ix Tested by an independent third-party test lab following MIL-STD-810H.
 x FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options. mutually exclusive options.
- Available when barcode reader option is selected. Available with limited configurations. xi
- xii
- xiii Drop test results vary from configurations and optional accessories.

Fully Rugged **Tablet**



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	2	2
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	4	4
LAN	1	1
HDMI	1	1
RF Antenna Connector	3 (GPS, WWAN, WLAN)	



GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 11568, Taiwan, R.O.C. Tel : +886 2 2785 7888 globalmarketing@getac.com | www.getac.com



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved tion provided herewith is for reference only available specification shall be subjected to quotation by request. V01M05Y21WW