



# ZX70 December of the providence of the providenc

- Qualcomm<sup>®</sup> Snapdragon<sup>™</sup> 660, Octa-core Processor
- Verified as Android Enterprise Recommended <sup>i</sup>
- 7" LumiBond<sup>®</sup> Display with Getac Sunlight Readable Technology and Glove-enabled Capacitive Touchscreen
- 6 Feet Drop, MIL-STD-810H and IP67 Certified
- Optional Barcode Reader, RFID Reader





### **Rugged Mobile Computing Solutions**

## Specifications

### **Operating System**

Android<sup>™</sup> 10.0 **Mobile Computing Platform** Qualcomm<sup>®</sup> Snapdragon<sup>™</sup> 660, Octa-core 1.95GHz Max 2 2GHz

### VGA Controller

Qualcomm<sup>®</sup> Adreno<sup>™</sup> 512 GPU

### **Display**

7" IPS TFT LCD HD (1280 x 720) Protection film LumiBond® display with Getac sunlight readable technology Capacitive multi-touch screen

### **Storage & Memory** 4GB LPDDR4

64GB eMMC

### **Keyboard**

Power button 3 tablet programmable buttons

### **Pointing Device**

Touchscreen - Capacitive multi-touch screen

### I/O Interface

8M pixels webcam x 1 12M pixels auto focus rear camera x 1 DC in Jack x 1 USB 2.0 (Host) x 1 MicroUSB 2.0 (Client) x 1 MicroSD x 1 Docking Connector (Pogo/JAE) x 1 Optional: RF antenna pass-through for GPS and WWAN

### **Communication Interface**

Wi-Fi 802.11ac Bluetooth (v5.0) Dedicated GPS Optional: 4G LTE mobile broadband

### **Security Feature**

Optional: Contactless HF RFID / NFC combo reader <sup>iii, iv</sup> Optional: Barcode reader

### Power

AC Adapter (25W, 100-240VAC, 50/60Hz) Li-Ion battery (3.8V, typical 8480mAh; min. 8220mAh)

### Dimension (W x D x H) & Weight

218 x 142 x 27mm (8.58" x 5.6" x 1.08") 762g (1.68lbs)

### **Rugged Feature**

MIL-STD-810H certified IP67 certified Vibration & 6 feet (1.8m) drop resistant vii Optional: ANSI / UL 121201, CSA C22.2 NO. 213

### **Environmental Specification**

- Temperature vi
- Operating: -21°C to 60°C / -6°F to 140°F
- Storage: -40°C to 71°C / -40°F to 160°F Humidity
- 95% RH, non-condensing

### **Pre-installed Software** Getac File Brower

Getac Camera Getac Input Method DeployeXpress Client Getac Settings and Google Applications (Search, Chrome, Gmail, Maps, YouTube, Play, Drive, Play Music, Play Movies, Duo and Photos) Accessories

AC Adapter (25W; 12V/2A, 100-240VAC; 50/60Hz) Capacitive Stylus Pen holder Wrist Strap

Optional:

Carry Bag AC Adapter (25W; 12V/2A, 100-240VAC; 50/60Hz) Office Dock AC Adapter (60W, 110-240VAC) Vehicle Adapter (40W, 11-16V, 20-32VDC) Capacitive Stylus Protection Film Shoulder Strap (2-point) Wrist Strap

Rotating Hand Strap with Kickstand and Stylus Holder

USB to RS232 Converter Cable Docking Connector to HDMI Converter Cable Vehicle Dock Office Dock

### Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. Standard

3 years Bumper-to-Bumper

- i Android Enterprise Recommended rugged devices deliver a consistent set of features verified by Google with an elevated device baseline, increased security standards and enterprise-focused features and behaviors to
- meet the needs of users. Google and Denavior to meet the needs of users. Google and Android are trademarks of Google LLC. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices. Users may hold be address of forth of devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is
- operating in the area. 13.56MHz Contactless HF RFID / NFC reader iii (ISO 15693, 14443 A/B, Mifare and FeliCa" compliant)
- HF RFID / NFC combo reader applies to US & EU. iv
- Wi Proprietation and optional accessories.
  Vi Tested by an independent third-party test lab following MIL-STD-810H.
  Vii Drop test results vary from configurations and optional accessories.
  - optional accessories.

# Fully Rugged **Tablet**



### **Docking Solutions**

	Getac-made Vehide Dock (JAE)	Havis Vehicle Dock (Pogo,power only)	Havis Vehicle Dock (JAE)	Gamber-Johnsor Charging Cradle (Pogo)	n Havis Vehide Dock (Pogo)	Office Dock (JAE)	Office Dock (Pogo)
Serial Port	1		1		1		
Speaker	1			-	-		
Audio Output	1	1	1		1	1	1
DC in Jack	1	1	1	1	1	1	1
USB	USB Host x 2		USB2.0 x 2		USB2.0 x 2	USB Host x 2 MicroUSB Client x 1	USB Host x 2
LAN	1		1	-	1	1	1
HDMI	1		1	-	-	1	
RF antenna connector	(WWAN, GPS)	(WWAN, GPS)	(WWAN, GPS)		(VVWAN, GPS)		



### GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 11568, Taiwan, R.O.C. Tel : +886 2 2785 7888 globalmarketing@getac.com | www.getac.com



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved tion provided herewith is for reference only available specification shall be subjected to quotation by request. V01M05Y21WW