Getac

ZX70-EX
FULLY RUGGED TABLET

- Qualcomm® Snapdragon™ 660, Octa-core Processor

- Verified as Android enterprise recommended [i]

- 7" LumiBond® display with Getac sunlight readable technology and glove-enabled capacitive touchscreen

- 6-ft drop, MIL-STD-810H and IP67 certified

- Optional barcode reader and HF RFID

- ATEX & IECEx explosive atmosphere certified

CERTIFIED MIL-STD 810H | INGRESS PROTECTION IP67 | 6' Drop | ATEX Ex | IEC | IECEx

ZX70-EX handstrap with stylus holder

Volume control button
Power button
Barcode launch button
Optional: Contactless HF RFID / NFC combo reader
8MP webcam
12MP rear camera
Optional: 1D/2D imager barcode reader
USB host
Micro USB client
Micro SD card slot
Optional: SIM card slot x 1 (Micro-SIM, 3FF)
DC in Jack

Rugged Mobile Computing Solutions

Specifications

ZX70-EX
Fully Rugged
Tablet

Operating System
Android™ 10.0

Mobile Computing Platform
Qualcomm® Snapdragon™ 660, Octa-core 1.95GHz
Max. 2.2GHz

VGA Controller
Qualcomm® Adreno™ 512 GPU

Display
7" IPS TFT LCD HD (1280 x 720)
Anti-static protection film
LumiBond® display with Getac sunlight readable
technology
Capacitive multi-touch screen

Storage & Memory
4GB LPDDR4
64GB eMMC

Keyboard & Buttons
Power button
3 tablet programmable buttons

Pointing Device
Touchscreen
 - Capacitive multi-touch screen

Expansion Slot
Optional: 1D/2D imager barcode reader

I/O Interface
8M pixels webcam x 1
12M pixels auto focus rear camera x 1
DC in Jack x 1
USB 2.0 (Host) x 1
MicroUSB 2.0 (Client) x 1
MicroSD x 1
Optional: SIM card slot x 1 (Micro-SIM, 3FF)

Communication Interface
Wi-Fi 802.11ac
Bluetooth (v5.0) [ii]
Dedicated GPS
Optional: 4G LTE mobile broadband [iii]

Security Feature
Optional: HF RFID / NFC combo reader [iv, v]

Power
AC adapter (25W, 100-240VAC, 50/60Hz)
Li-ion battery (3.8V, typical 8480mAh; min.
8220mAh)

Dimension (W x D x H) & Weight
218 x 142 x 27mm (8.58" x 5.6" x 1.08")
774g (1.71lbs) [vi]

Rugged Feature
MIL-STD-810H certified
IP67 certified
Vibration & 6ft (1.8m) drop resistant [vii]
ATEX & IECEx certified

Environmental Specification
Temperature [viii]:
 - Operating: -21°C to 60°C / -6°F to 140°F
 - Storage: -40°C to 71°C / -40°F to 160°F
Humidity:
 - 95% RH, non-condensing

Explosion Protection
ATEX/IECEx Zone 2/22
Ex II 3G Ex ic op is IIC T5 Gc
Ex II 3D Ex ic op is IIIB T100°C Dc

Pre-installed Software
Getac File Browser
Getac Camera
Getac Input Method
Getac deployeXpress Client
Getac settings and Google applications (Search,
Chrome, Gmail, Maps, YouTube, Play, Drive, Play
music, Play movies, Duo and photos)

Optional Software
Getac Driving Safety Utility
Getac deployXpress
Getac OEMConfig

Accessories
AC adapter (25W; 12V/2A, 100-240VAC; 50/60Hz)
Capacitive stylus with tether
Pen holder
Wrist strap

Optional:
AC adapter (25W; 12V/2A, 100-240VAC; 50/60Hz)
Capacitive stylus with tether
Hand strap with stylus holder
Wrist strap
Pen holder

Bumper-to-Bumper Warranty
Accidents can take your equipment out of service
when you least expect it, especially in a rugged
environment, which can cause costly equipment
downtime.

That is why Getac has introduced accidental
damage as standard under our Bumper-to-Bumper
warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your
unit back in service within days.

Standard
3 years Bumper-to-Bumper

---

i   Android enterprise recommended rugged
devices deliver a consistent set of features
verified by Google with an elevated device
baseline, increased security standards and
enterprise-focused features and behaviors to
meet the needs of users. Google and Android
are trademarks of Google LLC.

ii   Bluetooth performance and connectable
distance may be subject to interference with
the environments and performance on client
devices, users may be able to reduce effects of
interference by minimizing the number of
active Bluetooth wireless devices that is
operating in the area.

iii Units with 4G LTE option comes with an
embedded SIM card slot.

iv 13.56MHz HF RFID / NFC reader (ISO 15693,
14443 A/B, Mifare and FeliCa™ compliant).

v   HF RFID / NFC combo reader applies to US & EU.

vi Weight and dimensions vary from
configurations and optional accessories.

vii Drop test results vary from configurations and
optional accessories.

viii Tested by an independent third-party test lab
following MIL-STD-810H.

Getac