

ST56D/O Field monitor catalogue

Specification

Description:	5.6" Ultra-High Resolution On-Camera Field Monitor
Model:	ST56D/O
Resolution	1280x800 pixels (up to1920x1440)
Brightness	220cd/m ²
Contrast:	500:1
Aspect Ratio:	16:10
Backlight:	LED
Response time:	30ms
Horizontal Frequency Range	30~75kHz
Field frequency range	60Hz~75Hz
Earphone output	Stereo,3.5mm Interface
HDMI Support Mode:	1080/50i/60i/50p/60p; 720/50p, 720/60p; 480i 480p, 576i 576p
Inputs:	Video,Audio,HDMI
Outputs:	HDMI;Built-in Speaker
Viewing Angle:	85°/85°(L/R) 85°/85°(U/D)
Power Consumption:	≤7W
Input Voltage:	DC 6~ 14V
Install Way:	1/4"-20 Thread Socket(2 sides up&down)
work Temperature:	-20°C ~ 50°C
storage Temperature:	-30°C~65°C
Unit Size:	162× 117W ×29H(mm)
Unit Weight:	306g 419g(With sun shade)

Standard Accessory	Optional Accessory	Packing Details	
Sony F970 Plate	Canon LP-E6 plate	Box size	24.6x24.4x8.7CM
Mini HDMI Cable	Panasonic D28 Plate	Per box G.W.	2.5kgs
Operation Manual	DC12V Power Adapter	Per Carton	10pcs
Hot Shoe Mount		Carton Size	50x44.5x27.4CM
Plastic Sunshade		N.W.	14kgs/carton
		G.W.	16kgs/carton