**Benefits**

- ▶ 1U keyboard drawer
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ Short depth design of 400mm
- ▶ Enhanced aesthetics with molded front panel and two point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)
- ▶ TAA Compliant

Options

- SUN Micro keyboard options available

Product Specifications

Console Port	
KB / MS	USB interface
	Drawer end : attached 6ft USB cable x 2
	Server end : USB type A x 2



Physical		
Dimensions (W x D x H)	Product	442 x 400 x 44 mm 17.4 x 15.7 x 1.73 inch
	Packing	582 x 500 x 100 mm 22.9 x 19.7 x 3.9 inch
Weight	Net	8.6 kg / 18.9 lb
	Gross	10.1 kg / 22.2 lb

* All dimensions stated are subject to change if options are selected / integrated to base model part codes


Mounting Distance	
Keyboard drawer	410 ~ 640 mm 16.1 ~ 25.2 inch

Environment	
Operating temp.	-20 to 65°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	10~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration


Compliance	
EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	REACH & RoHS3 / WEEE

Diagrams (mm)**Standard Keyboard**

Ge G keyboard with touchpad



Gb G keyboard with trackball

**Supporting layouts**

America		U.S.
EMEA		U.K. Germany France Russia Spain Italy
Asia		Japan Korea

Keyboard Options

* US layout only

Se S keyboard with touchpad

Sb S keyboard with trackball

