

SLP-88

Panel Mount Compact Backlit Keyboard

The panel mount SLP-88 by iKey features integrated backlighting that operates by pressing a light bulb key. It is housed in an ABS polycarbonate case that has 8-32 mounting studs. The SLP-88 is completely sealed and designed to meet NEMA 4X specifications. The waterproof and dustproof keyboard is ideal for industrial, kiosk and mobile computing applications. Constructed in a small-footprint compact case, the SL-88 allows for space saving and mobility. It is also available as the SLP-88-461, designed to meet MIL-STD-461G requirements.

Features:

- 12 Function Keys
- 88-Key Functionality
- Integrated Backlighting
- USB and PS/2 configurations available
- Meets MIL-STD-461G
- Optional NVIS Compliant – Green B backlighting



Product Code SLP-88

Certifications	NEMA 4X, CE UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axis
CABLE	LENGTH: 4 feet (1.2 meters) DESIGN: PS/2 or Single-Cable USB
Key Switch	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: 200mA@5V (from Keyboard port) USB: 200mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO
Compatibility	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	1.75 lbs +/-0.10 lbs (0.79 kg +/- 0.05 kg)
Warranty	1 Year Limited Warranty
Humidity	100% Humidity Resistant

Dimensions	11.80" x 6.79" x 1.35" (w-h-d) 299.7mm x 172.5mm x 34.3mm CUTOUT: 10.40" x 5.40" (w-h) 264.2mm x 137.2mm
------------	--

Model Numbers	SLP-88-PS2: With PS/2 cable SLP-88-USB: With USB cable
---------------	--