

Optional Accessories for Chassis

XWC-410030507220-RS



5.25" drive bay rack for 3.5" FDD or HDD, black, RoHS

Compatible models:
All IEI chassis with standard 5.25" drive bay

XWC-410030507230-RS



5.25" drive bay rack for 3.5" FDD or HDD, white, RoHS

Compatible models:
All IEI chassis with standard 5.25" drive bay

7G000-BA1110-RS



Removable drive bay for 3.5" IDE ATA-100/133 hard drive, RoHS
Dimensions (L x W x H) (mm):
220 x 126 x 28

Compatible models:
PAC-400G

7G000-ST1110-RS



Removable drive bay for 3.5" SATA hard drive, RoHS
Dimensions (L x W x H) (mm):
180 x 126 x 28

Compatible models:
PAC-400G

RHF-21-IDE-RS



3.5" IDE removable drive bay for 2.5" hard drive, RoHS

Compatible models:
All IEI chassis with standard 3.5" drive bay

32000-026800-RS



75 cm rounded IDE cable, RoHS

Compatible models:
RACK-1150G, RACK-1151G, RACK-3200G

32000-026900-RS



45 cm rounded IDE cable, RoHS

Compatible models:
RACK-1150G, RACK-1151G

32100-047401-RS



2 mm pitch USB cable, RoHS

Compatible models:
For front-accessible USB port on IEI chassis working with SBC using pitch 2.0mm USB connector onboard

XWC-3012025001-RS



12 cm ball bearing fan, max. 96.79 CFM, RoHS
MTBF: 50,000hrs
Operating Temperature: -5°C ~ 65°C

Compatible models:
RACK-360G

XWC-3008025020-RS



8 cm ball bearing fan, 42.2 CFM, RoHS
MTBF: 50,000hrs
Operating Temperature: -5°C ~ 65°C

Compatible models:
RACK-220G, RACK-2000G, RACK-1350G, RACK-3400G, RACK-305G, RACK-814G, RACK-3000G, RACK-3200G, RACK-500G, RACK-900G, RACK-3035G, PAC-42GF, PAC-1000G, PAC-106G, PAC-107G, PAC-1700G, PAC-125G, PAC-42GH, PR-1500G, PAC-400G, PAC-700G

XWC-3006025003-RS



6 cm ball bearing fan, 17.18 CFM, RoHS
MTBF: 50,000hrs
Operating Temperature: -5°C ~ 65°C

Compatible models:
RACK-1350G, RACK-305GATX, RACK-360GATX, PR-1300G

XWC-3004020003-RS



6 cm ball bearing fan, 8.16 CFM, RoHS
MTBF: 50,000hrs
Operating Temperature: -5°C ~ 65°C

Compatible models:
RACK-1150G, RACK-1151G, EBC-1000G

SLIDE-18



18" rackmount slide; for rackmount chassis with depth up to 500mm

SLIDE-24



24" rackmount slide; for rackmount chassis with depth over 500mm

EXTENDER-6



6" extender for 18" or 24" slide

1
Application
Server
Platform

2
Single
Board
Computer

3
IBX Series
POS PC

4
AFOLUX
POS
Panel PC

5
Video
Capture
Card

6
KAMIO
RISC

7
IOVU
Open HMI

8
VITO
Universal
Controller

9
DINO
BLADE

10
LCD
Product
Series

11
Embedded
System

12
Industrial
Computer
Chassis

13
Power
Supply

14
Peripherals