INDUSTRIAL KEYBOARDS & POINTING DEVICES

38 mm VANDALPROOF TRACKBALLS

TBS38- SBS38

This range of compact trackball units is highly ruggedized and designed for harsh industrial applications, kiosk consoles, navigation controls, etc... They feature a robust, vandalproof construction and all metal look : the carrier plate made of brushed stainless steel, a stainless steel ring protecting the trackball sealing and anti-vandal stainless steel IP65 sealed switches.

The 38mm trackball unit can either have :

• a black phenolic resin ball for highest resistance to hostile impacts and to scratches : Type TBS38F2

• a stainless steel ball for styling and complete stainless steel appearance : Type SBS38F2



SPECIFICATIONS

Sealing	: IP65 static	
Carrier plate	: brushed stainless steel	
Ball diameter	: 38,1 mm	
Ball material	: phenolic resin, black (TBS38F2)	
	stainless steel (SBS38F2)	
Dimensions	: 100 x 78 x 40 mm	
Weight	: 0,4 kg / 0,6 kg	
Tracking force: nom. 50 grams (TBS38F2)		
	nom. 65 grams (SBS38F2)	
Lifetime	: >= 2 million ball revolutions	
Cable	: shielded, straight 1,6 m long	
Operating temperature range : -10° C to $+60^{\circ}$ C		
Storage temperature range : $-25^{\circ}C$ to $+80^{\circ}C$		

Push button switch	es	
Sealing	: IP65	
Material	: stainless steel, brushed	
Mechanical life	: 1 mil. cycles min	
Contacts	: gold plated	
Travel	:1,3mm	
Operating force	: 4N typ	
Operating temperature $:-20^{\circ}C$ to $+60^{\circ}C$		

<u>CE</u> : compliant to EMC Directive 89/336/EEC for Electromagnetic Compatibility. Low Voltage Directive 73/23/EEC not applicable for our trackballs.

CONNECTIVITY

These combo PS/2 & USB trackball units have a 1,6 meter long shielded straight cable ended by a USB type A plug. An adaptor to PS/2 is added. No special device driver is needed, use standard available drivers of your operating system.

* Due to the increasing differences of the PS/2 mouse port specifications of the various PC manufacturers, we do recommend that this unit should be tested on the final PC configuration and operating system prior to installing it in series.

ORDER INFO

TBS38 F2	SBS38 F2
Phenolic Resin Ball	Stainless Steel Ball

Output : PS/2 & USB Combo

NSi

NSI bvba, Haakstraat 1A, B-3740 Bilzen, Belgium Tel. : +32 89 51 90 00 E-mail : info@nsi-be.com


www.nsi-be.com


INDUSTRIAL KEYBOARDS & POINTING DEVICES


38 mm VANDALPROOF TRACKBALLS

R5

DIMENSIONAL DRAWING







Dim in mm.

The company reserves the right to alter without prior knowledge the specification or design of any standard product or service.

