
# PANEL1173-841

17" TFT Expandable Intel® Core™2 Duo Industrial Panel Computer with 2 PCI Slots





- 1. COM 1 (RS-232/422/485)
- 2. DVI-I
- 3. Ethernet x 2
- 4. IEEE 1394a x 2
- 5. USB 2.0 x 4
- 6. Audio (Mic-in/Line-out)
- 7. COM 2/3 (RS-232) 8. Power switch

9. AC power 10. PCI slot x 2

#### **Features**



- 17" SXGA TFT LCD display
- Intel® Core™2 Duo processor
- Industrial-grade material front bezel: anti-corrosion
- Intel® Q965+ICH8 chipset
- Supports 2 PCI slots
- Built-in speakers & optional WLAN module
- Windows® Vista and 7 supported
- Supports panel mount and rack mount



#### Introduction

The PANEL1173-841 is a 17" Industrial panel PC which features Intel® Core™2 Duo processor and Intel® Q965 chipset to provide powerful computing performance. This panel PC also offers the expansion ability with 2 PCI slots. Further, the PANEL1173-841 adopts built-in speaker and WLAN module for wireless connectivity.

#### Powerful computing: Intel® Core™2 Duo processor

The PANEL1173-841 features Intel® Core™2 Duo with maximum FSB 1066 MHz and Intel® Q965+ICH8 chipset. It features two IEEE 1394a ports, two gigabit Ethernet and up to 4GB of dual-channel DDR2 system memory which deliver high computing capability for high performance-demanding applications.

#### Expandable for 2 PCI slots

The PANEL1173-841 has 2 PCI slots for expansion purpose. User can easily plug in standard half-size PCI cards such as motion card, communication card and so on.

#### Speaker & WLAN antenna supported

The PANEL1173-841 features built-in speaker, optional WLAN module and antenna for wireless network connectivity.

## **Specifications**

Front Dorol Industrial and democratical with ID/F/NEMA 4 massed and testing			
Front Bezel	Industrial-grade material with IP65/NEMA 4 rugged protection		
LCD Panel	Display Type	17" SXGA TFT	
	Brightness (cd/m²)	380 nits	
	Resolution	1280 x 1024 pixels	
	View Angle (H/V)	120°/140°	
Main system	CPU	LGA775 for Intel® Core™2 Duo/ Core™ Solo	
		processor with FSB 533/667/800/1066 MHz	

	Chipset	Intel® Q965 + ICH8
	System Memory	2 x 240-pin DDR2 DIMM max. up to 4 GB
	BIOS	Phoenix-Award 4Mbit with RPL/PXE LAN
		Boot ROM, SmartView and customer
		CMOS backup
	Storage	2 x 3.5" or 2 x 2.5" SATA HDD
	Drive	1 x slim CD-ROM
	\4/= + =  -   -  -   Ti =  -	255 January 4 255 and

O connector	2 x RS-232 (COM 2/3)
	1 x RS-232/422/485 (COM 1)
	2 x IEEE 1394a
	4 x USB 2.0
	2 x PS/2 keyboard/mouse
	2 x 10/100/1000Mbps Ethernet
	1 x DVI-I for display (a converter for DVI-I to VGA is
	included)
	1 x Audio (Mic-in/Line-out)
Expansion	2 x PCI slot
nterface	
Touchscreen	Resistive type
	Light Transmission 79%
	1 million activations (typical) at a single point
Power supply	100 ~ 240Vac, 250W
Dimensions	450 mm (17.71") (W) x 150 mm (5.9") (D) x
	370 mm (14.56") (H)
Weight (net/gross)	7.5 kg (16.5 lb)/11.3 kg (24.9 lb)
Environment	Operating temperature: 0°~ +40°C (32°~ 104°F)
	Relative humidity: 10 ~ 95% @ 40°C, non-condensing
	Operation vibration: 1.0G, 5~500Hz, random
Certification	CE

# **Ordering Information**

PANEL1173-841-R 17" TFT Intel® Core™2 Duo panel PC with 2 PCI slots

# **Optional Accessories**

82211730040E	2 x 3.5" HDD kit
82011750130E	2 x 2.5" HDD kit
82011750110E	Rack mount kit
82211530110E	Wireless LAN kit

## **Optional OS Installation**

Windows® 2000/XP/Vista

Touch Panel Computers for Various Industry

Digital Signage and Display

Medical Panel Computers

Medical Grade Monitors

GOT Fanless Touch Panel Computers

Touch Panel Computers for Infotainment


Touch Panel Computers for Automation

Touch Panel Monitors for Automation

Open Frame Panel Computers

Accessorie

## **Dimensions**



<sup>\*</sup> Specification and certifications are based on options and may vary.