

EDS-205A/208A Series

5 and 8-port unmanaged Ethernet switches



- > 10/100BaseT(X) (RJ45 connector), 100BaseFX (multi/single-mode, SC or ST connector)
- > Redundant dual 12/24/48 VDC power inputs
- > IP30 aluminum housing
- > Rugged hardware design well suited for hazardous locations (Class 1 Div. 2/ATEX Zone 2), Transportation (NEMA TS2/ EN 50121-4/e-Mark), and maritime environments (DNV/GL/LR/ABS/NK)
- > -40 to 75°C operating temperature range (T models)



Introduction

The EDS-205A/208A series are 5 and 8-port industrial Ethernet switches that support IEEE 802.3 and IEEE 802.3u/x with 10/100M full/half-duplex, MDI/MDI-X auto-sensing. The EDS-205A/208A switches provide 12/24/48 VDC (9.6 to 60 VDC) redundant power inputs that can be connected simultaneously to live AC/DC power sources. These switches have been designed for harsh industrial environments, such as in maritime (DNV/GL/LR/ABS/NK), rail wayside, highway, or mobile applications (EN 50121-4/NEMA TS2/e-Mark), or hazardous locations (Class I Div. 2, ATEX Zone 2) that comply with FCC, UL, and CE standards.

The EDS-205A/208A switches are available with a standard operating temperature range from -10 to 60°C, or with a wide operating temperature range from -40 to 75°C. All models are subjected to a 100% burn-in test to ensure that they fulfill the special needs of industrial automation control applications. In addition, the EDS-205A/208A switches have DIP switches for enabling or disabling broadcast storm protection, providing another level of flexibility for industrial applications.

Specifications

Technology

Standards:

IEEE 802.3 for 10BaseT
 IEEE 802.3u for 100BaseT(X) and 100BaseFX
 IEEE 802.3x for Flow Control

Processing Type: Store and Forward

Switch Properties

MAC Table Size:

EDS-205A: 1 K
 EDS-208A: 2 K

Packet Buffer Size:

EDS-205A: 384 kbit
 EDS-208A: 768 kbit

Interface

RJ45 Ports: 10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection

Fiber Ports: 100BaseFX ports (SC/ST connector, multi-mode, single-mode)

DIP Switches: Enable/Disable broadcast storm protection

Optical Fiber

		100BaseFX		
		OM1	Multi-Mode	Single-Mode
Fiber Cable Type			50/125 μm	G.652
Typical Distance		4 km	5 km	40 km
Wave-length	Typical (nm)	1300		1310
	TX Range (nm)	1260 to 1360	1280 to 1340	
	RX Range (nm)	1100 to 1600	1100 to 1600	
Optical Power	TX Range (dBm)	-10 to -20	0 to -5	
	RX Range (dBm)	-3 to -32	-3 to -34	
	Link Budget (dB)	12	29	
	Dispersion Penalty (dB)	3	1	

Note: When connecting a single-mode fiber transceiver, we recommend using an attenuator to prevent damage caused by excessive optical power.
Note: Compute the "typical distance" of a specific fiber transceiver as follows: Link budget (dB) > dispersion penalty (dB) + total link loss (dB).

Power Requirements

Input Voltage: 12/24/48 VDC redundant dual inputs

Operating Voltage: 9.6 to 60 VDC

Input Current: EDS-205A: 0.09 A @ 24 V

EDS-205A-M/S: 0.1 A @ 24 V

EDS-208A: 0.11 A @ 24 V

EDS-208A-M/S: 0.11 A @ 24 V

EDS-208A-MM/SS: 0.15 A @ 24 V

Overload Current Protection: 1.1 A

Connection: 1 removable 4-contact terminal block

Reverse Polarity Protection: Present

Physical Characteristics

Housing: Aluminum

IP Rating: IP30 protection

Dimensions:

EDS-205A Series: 30 x 115 x 70 mm (1.18 x 4.52 x 2.76 in)

EDS-208A Series: 50 x 114 x 70 mm (1.96 x 4.49 x 2.76 in)

Weight:

EDS-205A Series: 175 g (0.39 lb)

EDS-208A Series: 275 g (0.61 lb)

Installation: DIN-rail mounting, wall mounting (with optional kit)

Environmental Limits

Operating Temperature:

Standard Models: -10 to 60°C (14 to 140°F)

Wide Temp. Models: -40 to 75°C (-40 to 167°F)

Storage Temperature: -40 to 85°C (-40 to 185°F)

Ambient Relative Humidity: 5 to 95% (non-condensing)

Standards and Certifications

Safety: UL 508

Hazardous Location:

UL/cUL Class 1 Division 2 Groups A/B/C/D,

ATEX Zone 2 Ex nA IIC T4 Gc

EMC: EN 55032/24

EMI: CISPR 32, FCC Part 15B Class A

EMS:

IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV

IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m

IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV

IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV

IEC 61000-4-6 CS: 10 V

IEC 61000-4-8

Traffic Control: NEMA TS2

Rail Traffic: EN 50121-4

Marine:

EDS-205A: DNV, GL, LR, ABS, NK

EDS-208A: IEC 60945; Pending: DNV, GL, LR, ABS, NK

Shock: IEC 60068-2-27

Freefall: IEC 60068-2-32

Vibration: IEC 60068-2-6

Note: Please check Moxa's website for the most up-to-date certification status.

MTBF (mean time between failures)

Time:

EDS-205A Series: 3,040,784 hrs

EDS-208A Series: 2,701,531 hrs


Standard: Telcordia (Bellcore), GB

Warranty

Warranty Period: 5 years

Details: See www.moxa.com/warranty

Dimensions



Ordering Information

Available Models		Port Interface			
Standard Temperature (-10 to 60°C)	Wide Temperature (-40 to 75°C)	10/100BaseT(X)	100BaseFX		
			Multi-Mode, SC Connector	Multi-Mode, ST Connector	Single-Mode, SC Connector
EDS-205A	EDS-205A-T	5	-	-	-
EDS-205A-M-SC	EDS-205A-M-SC-T	4	1	-	-
EDS-205A-M-ST	EDS-205A-M-ST-T	4	-	1	-
EDS-205A-S-SC	EDS-205A-S-SC-T	4	-	-	1
EDS-208A	EDS-208A-T	8	-	-	-
EDS-208A-M-SC	EDS-208A-M-SC-T	7	1	-	-
EDS-208A-M-ST	EDS-208A-M-ST-T	7	-	1	-
EDS-208A-MM-SC	EDS-208A-MM-SC-T	6	2	-	-
EDS-208A-MM-ST	EDS-208A-MM-ST-T	6	-	2	-
EDS-208A-S-SC	EDS-208A-S-SC-T	7	-	-	1
EDS-208A-SS-SC	EDS-208A-SS-SC-T	6	-	-	2

Optional Accessories (can be purchased separately)

DR-4524/75-24/120-24: 45/75/120 W DIN-rail 24 VDC power supplies

MDR-40-24/60-24: 40/60 W DIN-rail 24 VDC power supplies, -20 to 70°C operating temperature

RK-4U: 4U-high 19-inch rack-mounting kit

WK-30: Wall-mounting kit, 2 plates with 4 screws (EDS-205A series only)

WK-46-01: Wall-mounting kit, 2 plates with 8 screws (EDS-208A series only)

Package Checklist

- EDS-205A or EDS-208A switch
- Hardware installation guide (printed)
- Warranty card