

Rugged Industrial PDA 4.3"

E430T

Product Features:

- 4.3" Sunlight Readable Panel with Projective Capacitive Multi-touch.
- Built-in Wi-Fi/ Bluetooth/ GPS / Optional 3G
- Built-in 2 Mega-pixel camera at front side and 5 Mega-pixel camera with LED at rear side
- Large capacity Li-poly 2400mAh Battery
- Water and dust proof ID IP66 design
- Compliance with MIL-STD-810F for High/Low temperature, Vibration, Drop test
- Support Android 2.3 operating system
- Optional Windows Mobile 6.5
- U-Blox GPS module

Product Specifications:

System Specification	Processor	TI Cortex A8 OMAP 1GHz		
	System Memory	512MB SDRAM		
	Storage	512MB NAND flash		
	Operating System	Android 2.3 (Default)		
		Windows Mobile 6.5 (optional)		
		Windows CE 6.0 (optional)		
Display Specification	Size	4.3"		
	Resolution	480 x 800		
	Brightness	270(typ.)		
	Touch	Projective Capacitive Multi-touch		
Wireless Communication	WLAN	802.11 b/g/n		
	Bluetooth	Bluetooth V2.1+EDR		
	WWAN	3.5G (optional)		
	GPS	Built-in GPS module		
Mechanical and Environment	Dimensions (W x L x H)	132.2 x 82 x 21.5 mm		
	Operation Temperature	-20°C ~60°C		
	Shock	Shock MIL-STD-810F M516.5		
	Vibration	Vibration MIL-STD-810F M514.5		
	Drop	MIL-STD-810F M516.5, 4 ft, Free to concrete		
	Certifications	CE, FCC,UL		
	Weight	220g (±1.5g)		
I/O Connectors	External I/O	1 x Micro USB 1 x 3.5mm Audio jack for Micphone and earphone		
	Internal I/O	1 x SIM card slot 1 x Micro SD card slot		
	Intenal Audio Device	1 x Microphone		
		1 x Earpiece 1 x Speaker		
In front Control	Control button	1 x Volume + 1 x Volume - 1 x Power button 1 x Function button 4 xCapactive buttons:Home/ Menu/ ESC/ Search functions		
		LED indicator	1 x LED indicator	
		Field Service	Light Sensor	Built-in
			Proximity (Light) Sensor	Built-in
	Power	Battery	3.7V 2400mAh Li-poly rechargeable battery	
Battery Operating Time		Low Use Case:8.6Hr(Backlight at 10% duty cycle,default level,idle)		
Adapter		5V 1A Adapter		



Order Information:

Model Name	Config
E430TG	3G (HSUPA)

Drawing

