



STAM1911LMA 19" Medical Display

- > ALS (optional)
- > Calibration mode(optional)

+ Spec

I/O	
RS232	Optional
Input Interface	2 x DVI 1 x Display Port 1 x VGA 1 x CVBS 1 x S-Video 1 x Sync-on-video/H/V 1 x USB HUB
Output Interface	1 x Sync-on-video
Mechanical & Environmental	
Power Type	AC In
Operating Temp	0°C ~ 40°C (32°F ~ 104°F)
Storage Temp	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	10%~90% Relative Humidity, Non-condensing
Weight	4.4 Kgs
Construction	Plastic
Mounting Kit	Stand (Optional) VESA Mount kit (Optional) Wall Mount kit (Optional)
Vibration Test	With SSD/mSATA: 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With SSD/mSATA: 10Grms, IEC 60068-2-27, Half Sine, 11ms
System Fan	Fanless
Dimension	412.4 x 338 x 73 mm
Certifications	
Certification Information	CE(EN60601-1,EN60601-1-12) FCC certified cTUVus certified
Panel	
LCD Size	19"
Display Type	SXGA
Resolution	1280 x 1024
Luminance	330 Cd/m2
Contrast ratio	1000:1
Viewing angle	89/89 Deg. Horizontal & Vertical
Backlight	LED
Touch Type	N/A
AG Protection Glass	Yes
DICOM compliant	Yes

+ Ordering

STAM1911LMA
STAM1911LMA w/o Glass or PCAP