



C71

Mobile Computer



Chainway C71 with abundant functions is an Android rugged mobile computer. With its powerful quad-core processor, stable wireless connections and comprehensive data capture options, you can find this easy-to-deploy device a valuable helper to increase productivity in logistics, warehousing, retail, identity verification, meter reading, IC card reading and etc.



Specification

Physical Characteristics	
Dimensions	164.2*78.8*17mm/6.46*3.10*0.67in (for standard version)
Weight	<288g/10.15oz (for standard version)
Display	5.2" IPS FHD 1920x1080
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Power	Main battery: Li-ion, rechargeable, built-in 5000mAh
	Standby: over 350 hours
	Continuous use: over 12 hours (depending on user environment) Charging time: 3-4 hours (with standard adaptor and USB cable)
Expansion Slot	1 slot for SIM card, 1 slot for SIM or TF card, three choice two
Interfaces	USB 2.0 Type-C, OTG
Audio	Speaker, 2 microphones
Keypad	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key
Sensors	Gravity sensor, light sensor, proximity sensor, vibration motor
Performance	
CPU	Cortex-A53 Quad-core 1.3GHz
RAM+ROM	2GB+16GB
Expansion	Supports up to 32 GB Micro SD card
Developing Environment	
Operating System	Android 6.0
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio
User Environment	
Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5%RH - 95%RH non condensing
Drop Specification	Multiple 1.8m/5.9ft drops (at least 20 times) to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5m/1.6ft falls at room temperature
Sealing	IP65/IP67 per IEC sealing specifications
ESD	±8KV air discharge, ±4KV conductive discharge
Communication	
WWAN	IEEE802.11 a/b/g/n, 2.4G/5G dual-band, internal antenna
	2G: 850/900/1800/1900MHz
	3G: 850/900/1900/2100MHz
WWAN(Europe)	4G: B1, B3, B5, B7, B8, B20, B40
	2G: 850/900/1800/1900MHz
	3G: 850/900/1700/1900MHz
WWAN(America)	4G: B2, B4, B7, B12, B17
	2G: 900/1800MHz
	3G: 900/1900/2000/2100MHz
WWAN (China)	4G: B1, B3, B5, B38, B39, B40, B41
	2G: 900/1800MHz
	3G: 900/1900/2000/2100MHz
WWAN (Others)	Depending on the country's ISP

Bluetooth	Bluetooth 4.0, BLE
GNSS	GPS/AGPS, GLONASS, BeiDou, internal antenna
Data Collection	
Camera	
Rear Camera	13MP Autofocus with flash
Front Camera (optional)	5MP camera
Barcode Scanning (optional)	
1D Linear Scanner	Zebra SE965 / Honeywell N4313
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Imager Scanner	Zebra: SE4710 / SE4750 / SE4750MR; Honeywell: N6603
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.
Iris (optional)	
Rate	<150ms
Range	20-40cm
FAR	1/10000000
Protocol	ISO/IEC 19794-6, GB/T 20979-2007
*Iris is alternative to front camera.	
HF (optional)	
Frequency	13.56MHz
Protocol	ISO14443A/B, ISO15693
Chips	M1 card (S50/S70), M0 (Ultralight), M3 (Desfire D40/D41/D81), CPU_A card, CPU_B card, ICODE II, T12048, LRI64K, Others for customization
Range	3-8cm
NFC (optional)	
Frequency	13.56MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4cm
UHF (optional)	
Frequency	865MHz-868MHz / 920-925MHz / 902-928MHz
* For detailed specification, please check C71 UHF data sheet	
InfraRed (optional)	
Frequency	38kHz
* For detailed specification, please check C71 InfraRed data sheet	
Fingerprint (optional)	
Sensor	Capacitive TCS1/TCS2; Optical Morpho CBM-E3
* For detailed specification, please check C71 Fingerprint data sheet	
PSAM (optional)	
Card slot	2 slots for PSAM cards
Protocol	ISO7816 T=0, T=1

Accessories(See details in Accessory Guide)



Cradle (Optional)



AC Adaptor



USB Cable



Holster

Notice: Product specifications are subject to change without prior notice. / Model: C71 / Update Date: 2018-08-23

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net