



# ZX70-Ex

### Fully Rugged Tablet

- 7" LumiBond® Display Sunlight Readable Technology and Glove-enabled Capacitive Touchscreen
- 6 Feet Drop , MIL-STD-810G and IP67 Certified
- Optional 2D Imager Laser Barcode Reader and RFID Reader
- Optional 4G LTE WWAN
- High Sensitivity GPS













## ZX70-EX Fully Rugged Tablet





### **Specifications**

**Operating System** Android 6.0

Intel Atom® Processor x5-Z8350 1.44GHz, **Mobile Computing Platform** 

burst up to 1.92 GHz - 2MB cache

Intel® HD Graphics VGA Controller

Display 7" IPS TFT LCD HD (1280 x 720)

LumiBond® display with Getac sunlight readable technology

Capacitive touchscreen with glove on

Storage & Memory 2GB LPDDR3 expandable to 4GB

eMMC 32GB / 64GB

Keyboard 4 tablet buttons ( Power, Barcode Launch Button,

Volume Up, Volume Down)

Pointing Device Touchscreen

- Capacitive multi-touch screen

I/O Interface MicroSD x1

FHD webcam x 1

8M pixels auto focus rear camera x 1

MicroUSB 2.0 (Client) x 1 USB 2.0 (Host) x 1

Docking connector (Pogo/JAE)

DC in Jack x 1 MicroSD x 1

Wi-Fi 802.11 n Communication Interface

Bluetooth (v4.0)i Dedicated GPS

Optional 4G LTE mobile broadband

Software Getac Settings, Google Chrome, Gmail, Google+,

Google Maps, Google Play Music, Google Play Movies, Google Play Books, Google Play Newsstand,

Google Play Games, Google Drive, YouTube, Google Plus Photos, Hangouts

Optional Contactless RFID/NFC combo reader ii, iii **Security Feature** 

. Optional Barcode reader

AC adapter (24W, 100-240VAC, 50 / 60Hz)

Li-Ion battery (3.8V, 8400mAh)

218 x 142 x 27 mm (8.58 " x 5.6" x 1.08") Dimension (W x D x H) &

780g (1.71lbs)vi Weight

MIL-STD-810G certified and IP67 certified **Rugged Feature** 

6 feet drop resistant Vibration & drop resistant e-Mark certified for vehicle usage

ATEX & IECEx Explosive Atmosphere Certified

**Environmental Specification** Temperaturevii:

- Operating: -21°C to 60°C / -6°F to 140°F - Storage: -40°C to 71°C / -40°F to 160°F

Humidity:

- 95% RH , non-condensing

Accessories Carry Bag

AC adapter (24W; 12V/2A, 100-240VAC; 50 / 60 Hz)

Capacitive stylus ZX70-Ex Hand strap

- 13.56MHz Contactless REID/NEC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- RFID/NFC combo reader applies to US & EU only.
- Weight and dimensions vary from configurations and optional accessories.

  Tested by a national independent third party test lab following MIL-STD-810G





#### **Getac Technology Corporation**

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 11568, Taiwan, R.O.C. Tel: +886 2 2785 7888 globalmarketing@getac.com www.getac.com

Copyright © 2017 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request. V02M06Y17WW

Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices. users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area