



# KEY TECHNOLOGY (CHINA) LIMITED

## 深圳市键特电子有限公司



Head Office: B702, Building 1, Tianan Cyber Park, Huang Ge North Road, Longcheng Subdistrict, Long Gang District, ShenZhen, Guang Dong, P.R.China

Factory ADD: 4 Floor, No.6, High-Tech Road, Baolong Industrial Zone, Longgang District, ShenZhen, Guang Dong, P.R.China

Tel: +86 755 89239859, 89230460, 85232807

Fax: +86 755 89312576



E-mail: info@key-tek.cn, sales01@key-tek.cn

Website: www.key-tek.cn, www.ikb-mkb.com

**MODEL NO.:** K-TEK-A83-38-MTB

**DESCRIPTION:** IP65 static rated vandal proof Stainless Steel industrial Trackball with IP65 static 38mm stainless steel mechanical trackball module with 400 DPI resolutions, trackball module protected and shielded by stainless steel housing, 3 mouse buttons designed for right & left clicking and scrolling up and down with ball rolling, rear panel mounted.

**DIMENSIONS:** 83.0mm x 110.0mm (front panel)





# KEY TECHNOLOGY (CHINA) LIMITED

## 深圳市键特电子有限公司



Head Office: B702, Building 1, Tianan Cyber Park, Huang Ge North Road, Longcheng Subdistrict, Long Gang District, ShenZhen, Guang Dong, P.R.China

Factory ADD: 4 Floor, No.6, High-Tech Road, Baolong Industrial Zone, Longgang District, ShenZhen, Guang Dong, P.R.China

Tel: +86 755 89239859, 89230460, 85232807

Fax: +86 755 89312576

E-mail: info@key-tek.cn, sales01@key-tek.cn

Website: www.key-tek.cn, www.ikb-mkb.com

### MAIN FEATURES

- Emulates most popular mice-uses existing mouse driver and mouse software Interfaces for most workstations and computers, just plug and play.
- All Metal Mechanicals provide for rugged, smooth, long lasting operation.
- 38mm Diameter Stainless steel or Hard Phenolic Resin Ball for smooth, durable operation and precise cursor positioning.
- Rate Sensitive Dynamic Resolution provides for accelerated movement of the cursor when the ball is moved fast, while retaining one-pixel positioning accuracy when the ball is moved slowly.
- Teflon Ball Shields are available for dirt and water protection in harsh environments.

### TECHNICAL SPECIFICATION

ITEM	SPECIFICATION	
Mechanical	Key	3 keys, quality brushed stainless steel
	Key top style	Protuberant Rectangular Keys,
	Front Plate	Quality brushed stainless steel
	Key Travel	2.0mm
	Ball diameter	38.1mm/1.50" (19mm, 25mm, 36mm 40mm also available)
	Key switch lifespan	more than 10 Mio actuations
	Track ball lifespan	> 10 Mio revolutions
	Back Metal Cover	Rear side integrated electronics protected by a metal cover
	Actuation Force	1.0N to 3.0N
	Mounting Rack	Aluminum alloy
	Dimension	Dimensions with 38mm track ball, Front plate (W x H): 83.0 x 110.0mm, Back panel (W x H): 107.0 x 134.0mm
Interface	PS2, USB are available, Y type cable with ports of PS2 and USB	
Electrical	Power supply	5V DC $\pm$ 10%, keyboard interface
	Protection level	IP65 (front panel), NEMA3
	EMC Standard	EN55022(B)
	Power consuming	$\leq$ 1.00W(dynamic)
		$\leq$ 0.2W(static)
Contact Material	Gold/Carbon	
Environmental	Operating temperature	-20°C~+ 60° C





# KEY TECHNOLOGY (CHINA) LIMITED

## 深圳市键特电子有限公司



Head Office: B702, Building 1, Tianan Cyber Park, Huang Ge North Road, Longcheng Subdistrict, Long Gang District, ShenZhen, Guang Dong, P.R.China

Factory ADD: 4 Floor, No.6, High-Tech Road, Baolong Industrial Zone, Longgang District, ShenZhen, Guang Dong, P.R.China

Tel: +86 755 89239859, 89230460, 85232807

Fax: +86 755 89312576

E-mail: info@key-tek.cn, sales01@key-tek.cn

Website: www.key-tek.cn, www.ikb-mkb.com

	Storage temperature	- 30°C~+ 70°C
	Operating RH	30~90%
	Atmospheric pressure	60~106Kpa.
Reliable	Certificates	RoHS compliant, CE and FCC certified.
	MTBF	>50000h
	MTTR	< 30min
<b>OS</b>	<b>OS is under All windows, Linux, Unix, Mac OS9 / OSX</b>	
Packing Details	Each unit to a suitable brown box, suitable brown boxes to a standard export carton.	

