



KEY TECHNOLOGY (CHINA) LIMITED

深圳市键特电子有限公司



Head Office: B702, Building 1, Tianan Cyber Park, Huang Ge North Road, Longcheng Subdistrict, Long Gang District, ShenZhen, Guang Dong, P.R.China

Factory ADD: 4 Floor, No. 6, High-Tech Road, Baolong Industrial Zone, Longgang District, ShenZhen, Guang Dong, P.R.China

Tel: +86 755 89239859, 89230460, 85232807

Fax: +86 755 89312576


E-mail: info@key-tek.cn, sales01@key-tek.cn

Website: www.key-tek.cn, www.ikb-mkb.com

Model NO: K-TEK-M375KP-FN-DT

DIMENSIONS : 379.0mm x 142.8mm x 15.5mm (L x W x H)

DESCRIPTION: 106 keys IP68 dynamic sealed & ruggedized industrial silicone rubber Hygienic keyboard, integrated sealed numeric keypad, function keys and industrial PCB with carbon-on-gold key switch technology with long stroke (1.50mm) with extremely good tactile feeling for fast and accurate data input without any noise, with durable coating & antimicrobial keyboard surface withstand to most chemicals and liquids under harsh environment, Clean key for easy cleaning via locking/disable the whole keyboard without needing to take away the keyboard from PC, panel mounted solution, movable stand alone desk top version, adjustable industrial backlight optional.





KEY TECHNOLOGY (CHINA) LIMITED

深圳市键特电子有限公司



Head Office: B702, Building 1, Tianan Cyber Park, Huang Ge North Road, Longcheng Subdistrict, Long Gang District, ShenZhen, Guang Dong, P.R.China
Factory ADD: 4 Floor, No. 6, High-Tech Road, Baolong Industrial Zone, Longgang District, ShenZhen, Guang Dong, P.R.China

Tel: +86 755 89239859, 89230460, 85232807

Fax: +86 755 89312576

E-mail: info@key-tek.cn, sales01@key-tek.cn

Website: www.key-tek.cn, www.ikb-mkb.com

APPLICATIONS:

This keyboard provides full-size versatility in a rugged, compact design with the added convenience of an integrated numeric keypad. For working in low-light areas, it is also available with optional LED backlighting. Engineered for NEMA 4X protection from dust, water and corrosive liquids. This keyboard is ideal for use in environments ranging from manufacturing to material handling to medical settings. Its numeric pad allows for easy data entry.

MEDICAL: lab, hospital, clinic, dental, such as carts, diagnostic equipments, operation rooms, dialysis centers etc;

MATERIAL HANDLING: mobile keyboard, data entry, assembly line etc

MILITARY: Army, Navy, Air force

INDUSTRIAL: Industrial automation, pharmaceutical, oil and gas, **food and beverage**, clean or dirty manufacturing environments, warehouses

OTHER INDUSTRIES

MAIN FEATURE:

keyboard with NVIS-compliant red adjustable backlighting optional, while NVIS backlighting makes this keyboard ideal for aviation or vehicle applications where night vision goggles are necessary.

Keyboard provides full-size versatility in a rugged, compact design, rugged construction for reliable functionality

The keyboard lacks the crevices found between the keys of a regular keyboard, which is protected against dust, dirt, grease and corrosive liquids to NEMA 4X, which means it can withstand directed hose water, disinfectants, environmental contaminants and heavy industrial use.

Special durable-coating for excellent mechanical and chemical resistance

Clean key

-Prevents data from being sent while the keyboard is wiped down, allowing user to clean at any interval with minimal downtime

-User is notified of 'lock down mode' by brightly lit CLEAN KEY

With firm tactile key feel, key travel 1.50mm key travel.

Integrated numeric keypad.

Ease of customizing with multiple languages, to accommodate foreign or custom variants.

PS/2, USB connection cables that plug directly into computer like keyboard operations.

Enclosure: industrial silicone, Aluminum (rear side).

MECHANICAL DATA

Key: 106 keys

Key top style: Protuberant rectangular keys with tactile feeling.

Key Size: 12.0mm X 13.0mm for normal keys, 23.4mm x 13.0mm for enter key and 68.0mm x 13.0 mm for space bar key.

Switch life: more than 10 million of operations.

Cable Length: 2.50m

G.W.: 0.80KGs

Dimensions: 379.0mm x 142.8mm x 15.5mm (L x W x H)





KEY TECHNOLOGY (CHINA) LIMITED

深圳市键特电子有限公司



Head Office: B702, Building 1, Tianan Cyber Park, Huang Ge North Road, Longcheng Subdistrict, Long Gang District, ShenZhen, Guang Dong, P.R.China

Factory ADD: 4 Floor, No. 6, High-Tech Road, Baolong Industrial Zone, Longgang District, ShenZhen, Guang Dong, P.R.China

Tel: +86 755 89239859, 89230460, 85232807

Fax: +86 755 89312576

E-mail: info@key-tek.cn, sales01@key-tek.cn

Website: www.key-tek.cn, www.ikb-mkb.com

ELECTRICAL DATA

Supply Voltage: +5V DC +/-5%

Current Rating: 20mA (non-backlight) , 130mA (with backlight on)

EMC Standard: IEC61000-4-2:2008; IEC61000-4-3:2006+AI:2007+A2:2010; IEC 61000-4-4:2004

EMI: EN55022: 2010

EMS: EN55024: 2010

Lifespan > 3 years

Switch Contact Material: Carbon-on-Gold key switch technology with gold PCB.

Interface: PS2, USB available.

OS: All Windows, Linux, Unix, Mac OSX

ENVIRONMENTAL ADAPTABILITY

Operating temperature: -20°C to +60°C

Storage temperature: -30°C to +70°C

Humidity: 100%

Atmospheric pressure: 60-106Kpa

Shock: 3x11 ms pulses of 50g on each of 3 axes

Vibration: POWER SPECTRAL DENSITY: 0.04g/Hz, FREQUENCY RANGE: 20Hz - 2kHz, DURATION OF TEST PER AXIS: 3 hours

Flammability

PRINTED CIRCUIT BOARD: 94 VOSILICONE OVERLAY: 94 HBINTERFACE CABLE: 94 V

RELIABILITY

RoHS , CE, FCC, ESD

Protection Level: IP68, NEMA 6P

Key Lifespan >10 million actuations

MTBF >50000H

MTTR <30min

