



KEY TECHNOLOGY (CHINA) LIMITED

深圳市键特电子有限公司



Head Office: B702, Building 1, Tianan Cyber Park, Huang Ge North Road, Longcheng Subdistrict, Long Gang District, ShenZhen, Guang Dong, P.R. China

Factory ADD: 4 Floor, No. 6, High-Tech Road, Baolong Industrial Zone, Longgang District, ShenZhen, Guang Dong, P.R. China

Tel: +86 755 89239859, 89230460, 85232807

Fax: +86 755 89312576

E-mail: info@key-tek.cn, sales01@key-tek.cn

Website: www.key-tek.cn, www.ikb-mkb.com

Model NO: K-TEK-M64-OMS-DT

DIMENSIONS : 64.0mm x 126.0mm x 34.0mm (L x W x H)

DESCRIPTION: IP68 dynamic sealed & Ruggedized 5 keys Waterproof, Hygienic Optical Mouse with durable coating & antimicrobial mouse surface withstand to most chemicals and liquids under harsh environments, the mouse is full sized and features a 5-buttons designed for right & left clicking and scrolling up and down just like a conventional non-waterproof mouse, and it is a fully sealed IP68 and compatible with both USB and PS/2.



MAIN FEATURES:

- Optical IP68 mouse, 800DPI resolutions
- No raised or recessed surfaces
- Suitable for moist and dusty environments
- Three extra buttons for effortless scroll up, scroll down & scroll lock
- Excellent soft-touch tactile key response
- Special Dura-coating for excellent mechanical and chemical resistance
- Cable Length: 2.5m
- G.W.: 0.30KGs
- Dimensions: 64.0mm x 126.0mm 34.0mm (L x W x H)

ELECTRICAL DATA

- Supply Voltage: +5V DC +/-5%
- Current Rating: 100mA
- EMC Standard: It is compliance with the council IEC 61000-4-2:2008; IEC 61000-4-3:2006+A1:2007+A2:2010; IEC 61000-4-4:2004





KEY TECHNOLOGY (CHINA) LIMITED

深圳市键特电子有限公司



Head Office: B702, Building 1, Tianan Cyber Park, Huang Ge North Road, Longcheng Subdistrict, Long Gang District, ShenZhen, Guang Dong, P.R. China

Factory ADD: 4 Floor, No.6, High-Tech Road, Baolong Industrial Zone, Longgang District, ShenZhen, Guang Dong, P.R. China

Tel: +86 755 89239859, 89230460, 85232807

Fax: +86 755 89312576

E-mail: info@key-tek.cn, sales01@key-tek.cn

Website: www.key-tek.cn, www.ikb-mkb.com

EMI: EN 55022: 2010

EMS: EN 55024: 2010

Lifespan > 3 years

Switch Contact Material: Mechanical Switch.

Interface: PS2, USB available.

OS: All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

ENVIRONMENTAL ADAPTABILITY

Operating temperature: -20°C to +60°C

Storage temperature: -30°C to +70°C

Humidity: 100%

Atmospheric pressure: 60-106Kpa

Flammability

PRINTED CIRCUIT BOARD: 94 VO

SILICONE OVERLAY: 94 HB

INTERFACE CABLE: 94 V

RELIABILITY

RoHS Compliant, CE and FCC, ESD

Protection Level: IP68, NEMA 6P

Key Lifespan > 5 million actuations

MTBF > 50000H

MTTR < 30min

