

RUBBER KEYBOARDS

RKCT92

92 KEY RUBBER BACKLIT KEYBOARDS WITH 25 mm TRACKBALL IP67 sealed



GENERAL TECHNICAL SPECIFICATIONS

Sealing Keys Pointing Device Output Power requirements	: IP67 sealed : 92 rubber keys : 25 mm laser trackball : one 1,8 m. USB cable : Directly from USB port
u	
•	
	: Directly from USB port
Operating temp.	: 0°C to +60°C
Switch force	: 210 grams
Switch stroke	: 2 mm
Lifetime switches	: 2 million actuations

ORDER INFO

LAYOUT US Qwerty	PANEL MOUNT RKCT92F1	ENCLOSED RKCT92S1	
		2	ł

NSI presents their first standard silicone rubber keyboard. This 92 key backlit keyboard features a compact full MF rubber keyboard with integrated waterproof 25 mm laser trackball and scroll function.

The rubber keys are proven for efficient cleaning, reduced disinfection time and protection against cross contamination. The backlit keys warrant for optimized performance while working in low-light environments.

MAIN FEATURES

- Compact layout
- Removable 25 mm laser trackball
- Backlighting, dimmable
- Illumination of the key legends
- Low power LED's warrant for a long life
- No external power supply necessary, keyboard port power sufficient
- Dimmable backlighting at 8 levels by two dedicated keys
- Intelligent luminosity setting of "capslock" LED's
- White backlighting as standard, other colours on request.

Panel mount version :

- Front panel mounting with studs
- Dimensions / weight : 350 x 159 x 36 mm/ 0,6 kg

Enclosed version :

• Dimensions / weight : 353 x 162 x 40 mm / 0,8 kg



KEYBOARDS & POINTING DEVICES FOR THE MOST DEMANDING JOBS

RUBBER KEYBOARDS

RKCT92

92 KEY RUBBER BACKLIT KEYBOARDS WITH 25 mm TRACKBALL IP67 sealed

DIMENSIONAL DRAWING

Panel mount version



The company reserves the right to alter without prior knowledge the specification or design of any standard product or service.

VER. 1.0